

## Referencias

- Alberro, J. (1975). "Aplicaciones del método de elementos finitos. En presas de tierra y enrocamiento". *Ira edición. R. Marsal y D. Reséndiz, eds., Limusa, México*, pp. 317-338.
- Alonso E. E. (2003), "Exploring the limits of unsaturated soil mechanics: the behavior of coarse granular soil and rockfill". *The Eleventh Spencer J. Buchanan Lecture*.
- Alonso E. E., Gens A. and Josa A. (1990), "A constitutive model for partially saturated soils", *Géotechnique*, 40(3), pp. 405-430.
- Alonso E. E. y Odecop L. (2000). "Comportamiento de pedraplenes y escolleras". *Simposio sobre Geotecnia de las infraestructuras del Transporte*, pp. 843-859.
- E. E. Alonso, S. Olivella and J. Hugas (2003), "Modelling the behaviour of an earth and rockfill during construction and impoundment". *International Conference 'From Experimental Evidence towards Numerical Modelling of Unsaturated Soils'*, Weimar, Germany, in press.
- ASTM standards (2002), Volume 04.08 - Soil and Rock (I). Philadelphia.
- Balasubramaniam A.S., Ratnayake A.M.P., Phien-wej N. and Lee Y.H. (1991), "Deformation characteristics of rockfill materials", *7th International Congress on Rock Mechanics*, Aachen, Germany, pp. 187-194.
- Baldi G. Hight D. W., and Thomas G. E. (1988), "A Reevaluation of conventional triaxial test methods", *Advanced Triaxial Testing of Soils and Rock*, ASTM SPT 977, Rober T. Donaghe, Ronald C. Chaney, and Marsall L. Silver, Eds., American Society of Tesisting and Materials, Philadelphia, pp. 219-263.
- Baldi G. and Nova R. (1984), "Membrane penetration effects in triaxial testing", *Journal of Geotechnical Engineering*, vol. 100, No 3, pp. 403-420.
- Bathurst R. J. and Karpurapu R. (1993), "Large-scale triaxial compression testing of geocell-reinforced granular soils", *Geotechnical Testing Journal*, GTJODJ, Vol. 16, No. 3, pp. 296-303.
- Been K. and Jeffries M. G. (1985), "A state parameter for sands", *Géotechnique* 35(2), pp. 99-112.

Been K., Jefferies M. G. and Hachey J, (1991), "The critical state of sands", *Géotechnique* 41(3), pp. 365-381.

Biarez J. and Hicher P. (1994). "Elementary mechanics of soil behaviour. Saturated remoulded soils". Balkema, Rotterdam.

Biarez J. and Hicher P. (1997), "Influence de la granulométrie et de son évolution par ruptures de grains sur le comportement mécanique de matériaux granulaires", *Revue française de génie civil*, vol. 1, No. 4 pp. 607-631.

Carol I. and Prat P. C. (1995). "A multicrack model based on the theory of multisurface plasticity and two fracture energies", *Computational Plasticity*, Proceedings of the 4<sup>th</sup> International conference, pp. 1583-1595.

Chávez C. (1996), "Rotura de partículas en materiales granulares", *Tesis de Maestría* UACH. México.

Chávez C. and Alonso E. E. (2003). "A constitutive model for crushed granular aggregates which includes suction effects". *Soils and Foundations*, Vol. 43 No. 4, pp. 215-227.

Chen W. F. and Mizuno E. (1990). "Nonlinear analysis in soil mechanics theory and implementation". Elsevier science publishers B. V.

Coop M. R.(1990), "The mechanics of uncemented carbonate sands". *Géotechnique*, 40(4), pp. 607-626.

Coop M. R. and Lee I. K. (1995), "The influence of pore water on the mechanics of granular soils". *Proceedings XI ESMFE*, vol. 1 Copenhagen, pp. 63-72.

Coussy, O. (1995), "Mechanics of porous continua", John Wiley & Sons Ltd. Chichester.

Daouadji A. and Hicher P.Y. (1997), "Modelling of breakage influence on mechanical behavior of sands". *NUMOG VI*, Montreal, pp. 69-74.

De Josselin de Jong, G. (1971), "Rowe's stress-dilatancy relation based on friction", *Géotechnique* 26(3), pp. 527-534.

Desai C.S. (1980). "A general basis for yield, failure and potential functions in plasticity". *International Journal for Numerical and Analytical Methods in Geomechanics*, vol. 4, pp. 361-375.

Donaghe R. T., Chaney R.C. and Silver M. L. (1988), "Triaxial test for embankment dams: interpretation and validity", *Advanced Triaxial Testing of Soil and Rock*, ASTM SPT 977, pp. 486-500.

Duncan J. M. and Chang C. Y. (1970), "Nonlinear analysis of stress and strain in soils", *Journal of Soils Mechanics and Foundations Division*, vol. 96, SM5, pp. 1629-1653.

- Flora A. and Modoni G. (1997), "Upgrading equipment and procedures for stress path triaxial testing of coarse-grained materials", *Geotechnical Testing Journal*, GTJODJ, vol. 20, No. 4, pp. 459-469.
- Fumagalli, E. (1969), "Tests on cohesionless materials for rockfill dams", *Journal of Soils Mechanics and Foundations Division*, ASCE, No. SM1, pp. 313-330.
- Fredlund D. G. and Morgenstern N. R. (1977), "Stress state variables for unsaturated soils", *J. Geotech. Eng. Div.* GT5 ASCE, vol. 103, pp. 447-466.
- Gajo A. and Wood D. Muir (1999), "Seven-trent sand: a kinematic-hardening constitutive model: The  $q$ - $p$  formulation". *Géotechnique*, 49(5), pp. 595-614.
- Gere, J. M. y Timoshenko, S. P. (1986), "Mecánica de materiales", editorial Iberoamérica, 2<sup>a</sup> ed. México D.F.
- Goto S., Tatsuoka F., Shibuya S, Kim Y.S. and Sato T., (1991), "A simple gauge for local small strain measurements in the laboratory", *Soils and Foundations* vol. 31, No.1 pp. 169-180.
- Hardin B. O. (1985), "Crushing of soil particles", *Journal of Geotechnical Engineering* ASCE Vol. 111, No. 10, pp. 1177-1192.
- Hoque E., Sato T., and Tatsuoka F. (1997), "Performance evaluation of LDTs for use in triaxial tests". *Geotechnical Testing Journal*, GTJODJ, vol. 20, No. 2, pp. 149-167.
- Indraratna I., Wijewardena L. S. S. and Balasubramaniam A. S. (1993), "Large-scale triaxial testing of Greywacke rockfill", *Géotechnique* 43, No. 1, pp. 37-51.
- Jeefferies M. G. (1993). "Nor-sand: a simple critical state model for sand". *Géotechnique*, 43, No. 1, pp. 91-103.
- Kim M. K. and Lade P. V. (1988), "Single hardening constitutive model for frictional materials. I. plastic potential function", *Computers and Geotechnics*, vol. 5, pp. 307-224.
- Klotz E. U. and Coop M. R. (2002), "On the identification of critical state lines for sands". *Geotechnical Testing Journal*, vol. 25, No. 3, pp. 1-14.
- Kondner R. L. (1963). "Hyperbolic stress-strain response: cohesive soils". ASCE, SM1, vol. 47, no. 3, pp. 115-143.
- Konrad J. M. (1997), "In situ sand state from CPT: evaluation of a unified approach at two CANLEX sites", *Canadian Geotechnical Journal*, (34) pp. 120-130.
- Lade P. V. and Duncan J. D. (1975), "Elastoplastic stress-strain theory for cohesionless soils", *Journal of Geotechnical Engineering Division*, ASCE, vol. 101, No. GT10, pp. 1037-1053.

- Lade P. V. and Kim M. K. (1988), "Single hardening constitutive model for frictional Materials. II. Yield criterion and plastic work contours", *Computers and Geotechnics*, vol. 6, pp. 13-29.
- Lade P. V., Nelson R. B. and Ito Y. M. (1987), "Nonassociated flow and stability of granular materials", *Journal of Engineering Mechanics*, vol. 113, No. 9, pp. 1302-1318.
- Lagioia R., Puzrin A. M. and Potts D. M. (1996), "A new expression for yield and plastic potential surfaces". *Computers and Geotechnics*, vol. 19, no. 3, pp. 171-191.
- Lee I. K. and Coop M. R. (1995), "The intrinsic behaviour of decomposed granite soil", *Géotechnique*, 45(1), pp. 117-130.
- Lee L. K. and Farhoomand Y. (1967), "Compressibility and crushing of granular soil in anisotropic triaxial compression", *Canadian Geotechnical Journal*, vol. IV No. 1.
- Lee L. K. Seed H. B. and Dunlop P. (1967), "Effect of moisture on the strength of a clean sand". *Journal of the Soil Mechanics and Foundations Division*, ASCE SM6, pp. 17-40.
- Lekarp, F., Isacsson, U., and Dawson, A. (2000). "State of the art. I: Resilient response of unbound aggregates." *J. Transp. Engrg.*, ASCE, 126(1), 66-75.
- Lekarp, F., Isacsson, U., and Dawson, A. (2000b). "State of the art. II: Permanent strain response of unbound aggregates." *J. Transp. Engrg.*, ASCE, 126(1), 76-83.
- Leroueil S. (1997), "Critical state soil mechanics and the behaviour of real soils". *Symposium on Recent Developments in Soil and Pavement Mechanics*, Rio de Janeiro Brazil, pp. 1-40.
- Manzari M. T. and Dafalias Y. F. (1997), "A critical state two-surface plasticity model for sands". *Géotechnique* 47 (2), pp. 255-272.
- Marachi D., Chan C. K., Bolton Seed H. and Duncan J. M. (1969), "Strength and deformation characteristics of rockfill materials". Report No. TE-69-5 Department of Civil Engineering, University of California.
- Maranha das Neves E. (2002), "Algumas considerações sobre a mecânica dos enrocamentos", Conferência Pacheco Silva, Solos e Rochas, São Paulo, v. 25, n. 3, pp. 161-203.
- Maranha das Neves E. and Veiga Pinto A. (1988), "Modelling the collapse on rockfill dams". *Computers and Geotechnics*. vol. 6, pp. 131-153.
- Marsal, R. J. (1963). "Contact forces in soils and rockfill materials". *II Congreso Panamericano de Mecánica de Suelos e Ingenieria de Cimentaciones*, Brasil. Vol. II, pp 67-98.

- Marsal, R. J. (1963b). "Triaxial chamber for rockfill tests". *II Congreso Panamericano de Mecánica de Suelos e Ingenieria de Cimentaciones*, Brasil. Vol. I, pp. 99-122.
- Marsal, R. J. (1967). "Large scale testing of rockfill materials". *Journal of the Soil Mechanics and Foundations Division*, ASCE, 93, No. SM2, pp. 27-43.
- Marsal, R. J. (1969). "Contributions and discussions on mechanical properties of rock fill and gravel materials", Special Session No. 13. *VII International Congress of Soils Mechanics and Foundation Engineering*. México, D. F.
- Marsal, R. J. (1972), "Resistencia y compresibilidad de enrocamientos y gravas". Publicación No. 306 del Instituto de Ingeniería de la UNAM. México D. F.
- Marsal, R. J. (1973), "Mechanical properties of rockfill. In Embankment dam engineering. Casagrande volume (eds R. C. Hirschfel & S. J. Poulos), John Wiley & Sons, New Cork, pp. 109-200.
- Marsal, R. J. (1975). "Resistencia y compresibilidad de enrocamientos y gravas". En "Presas de Tierra y Enrocamiento". *Ira edición. R. Marsal y D. Reséndiz, eds.*, Limusa, México. Pp. 221-267.
- Marsal, R. J. (1975b). "Colocación y control de materiales en la cortina". En "Presas de Tierra y Enrocamiento". *Ira edición. R. Marsal y D. Reséndiz, eds.*, Limusa, México. Pp. 301-313.
- Marsal R. J., Arellano, L. R. Guzmán, M. A. y Adame, H. (1976), "El infiernillo. Behavior of dams built in Mexico". Instituto de Ingeniería, UNAM, México.
- McDowell G. R. (2000), "A family of yield loci base on micro mechanics". *Soils and Foundations* vol. 40, No. 6, pp 133-137.
- McDowell G. R., and Bolton M.D. (1998), "On the micromechanics of crushable aggregates". *Géotechnique* 48 (5), pp. 667-679.
- Miura N, Murata H. and Yasufuku N. (1984), "Stress- strain characteristics of sand in a particle- crushing region". *Soils and Foundations* vol. 24. No. 1, pp. 77-89.
- Miura N., and O-Hara S. (1979), "Particle-crushing of a decomposed granite soil under shear stress". *Soils and Foundation*, Vol. 19, No. 3, pp. 1-14.
- Nicholson P. G., Seed R. B. and Anwar H. A. (1993). "Elimination of compliance in undrained triaxial testing. I. Measurement and evaluation". *Can. Geotech. J.* (30) pp. 727-738.
- Nobari E. S. and Duncan J. M. (1972), "Effect of reservoir filling on stresses and movements in earth and rockfill dams". Report No. TE-72-1. Department of Civil Engineering, Institute of Transportation and Traffic Engineering, University of California.

Norma NLT-149/92. "Resistencia al desgaste de los áridos por medio de la máquina de Los Angeles". *Normas NLT II. Ensayos de Suelo*. 2<sup>a</sup> Edición, Cedex.

Norma UNE-EN 933-3, (1997). "Ensayos para la determinar las propiedades geométricas de los áridos. Parte 3: determinación de la forma de las partículas. Indice de lajas". AENOR.

Oldecop, L. (2000) "Compresibilidad de escolleras influencia de la humedad". *Tesis Doctoral*. Universidad Politécnica de Cataluña, España.

Oldecop, L. and Alonso, E. E. (2001). "A model for rockfill compressibility". *Geotechnique* 51 (2), pp. 127-140.

Olivella, S., A. Gens and A. Josa (1996). "Numerical formulation for a simulator (CODE\_BRIGHT) for the coupled analysis of saline media". *Engineering Computations*, vol. 13, no. 7, pp. 87-112.

Pallás, R. (1998) "Sensores y acondicionadores de señal". Marcomco boixareu editores, 3<sup>a</sup> edición.

Poorooshamb H., Holubec I. And Sherbourne A. (1966), "Yielding and flow of sand in triaxial compression part I", *Canadian Geotechnical Journal*, vol. III, No.4, pp. 179-190.

Poorooshamb H., Holubec I. And Sherbourne A. (1967), "Yielding and flow of sand in triaxial compression part II y III", *Canadian Geotechnical Journal*, vol. IV, No.4, pp. 376-397.

Potts D. M. and Zdravković L. (1999). "Finite element analysis in geotechnical engineering: theory". Thomas Telford.

Rahma A. (1996), "Modélisation du comportement du milieu granulaire en fonction de l'écrasement des grains", *Can. Geotech. J.* vol. 35, pp. 517-523.

Reséndiz D. y Romo M. (1975). "Relación entre el factor de seguridad y deformación de terraplenes". En "Presas de Tierra y Enrocamiento". 1ra edición. R. Marsal y D. Reséndiz, eds., Limusa, México, pp. 339-348.

Rowe, P. W. (1962), "The stress-dilatancy relation for static equilibrium of and assembly of particles in contact", *Proc. Roy. Soc. London A269*, pp. 500-527.

Santamarina J.C. and Cho G. C. (2004). "Soil behaviour: The role of particle shape". *Advances in Geotechnical Engineering: The Skempton Conference, 2004*. Vol. 1, pp. 604-617. Thomas Telford, London.

Schnitter, N. J. (1994), "A history of dams: the useful pyramids". Balkema, Rotterdam.

- Scholey, G.K., Frost, J.D., Lo Presti, D.C.F., and Jamiolkowski, M., (1995), "Instrumentation for measuring local strains during triaxial testing of small specimens", *ASTM Geotechnical Testing Journal*, Vol. 18, No. 2, pp. 137-156.
- Soriano, A. and Sánchez, F. J. (1999), "Settlements of railroad high embankments", *Proc. XII European Conf. on Soil Mech. and Geotech. Eng.*, Netherlands.
- Stewart, D. I., Tay, Y. Y. & Cousens, T. W. (2001), "The strength of unsaturated bentonite-enhanced sand", *Géotechnique* 51(9), pp. 767-775.
- Tatsuoka F and Ishihara K. (1974), "Yielding of sand triaxial compression", *Soils and Foundation*, vol. 14, No. 2, pp. 63-76.
- Terzaghi K., Ralph B. P. and Mesri Gholamreza (1996), "Soil mechanics in engineering practice", 3r ed., John Wiley & Sons.
- Ueng, T.-S. & Chen T.-J. (2000), "Energy aspects of particle breakage in drained shear of sands", *Géotechnique* 50(1), pp. 65-72.
- Veiga Pinto A. (1983), "Previsão do comportamento estructural de barragens de enrocamento", Laboratorio Nacional de Engenharia Civil, Lisbon, Tesis de doctorado.
- Vermeer, P. A. (1978), "A double hardening model for sand", *Géotechnique* 28, No. 4, pp. 413-433.
- Wan R. G. and Guo P.J. (1998), "A simple constitutive model for granular soils: Modified stress- dilatancy approach", *Computers and Geotechnics*, vol. 22. No. 2, pp. 109-133.
- Wan R. G. and Guo P.J. (1999), "A pressure and density dependent dilatancy model for granular materials", *Soils and Foundations*, vol. 39, No. 6, pp. 109-133.
- Wood D. M. (1990), "Soil behaviour and critical state soil mechanics", Cambridge University Press.
- Wood D. M., Belkheir K. and Liu D. F. (1994), "Strain softening and state parameter for sand modelling", *Géotechnique* 44 (2), pp. 335-339.
- Yamamoto J. A. Y Lade P. V. (1996), "Drained sand behaviour in axisymmetric tests at high pressures", *Journal of Geotechnical Engineering* 122 (2), pp. 109-119
- Yasufuku N., Murata H. and Hyodo M. (1991), "Yield characteristics of anisotropically consolidated sand under low and high stresses", *Soils and Foundations*, Vol. 31, No. 1, pp. 95-109.