

Referencias bibliográficas

(*) Corresponden a obras citadas en referencias consultadas.

Aki, K. (1968)*. “Seismic displacement near a fault”, Journal Geophys. Res., Vol. 73, 6, 5359-5376.

Alavi, B. y Krawinkler, H. (2000). “Consideration of near-fault ground motion effects in seismic design”, Proceedings of the 12th World Conference on Earthquake Engineering, Nueva Zelanda.

Ali, S. y Page, A. (1988)*. “Finite element model for masonry subjected to concentrated loads”, Journal of Structural Engineering, ASCE, 114, 8, 1761-1784.

Angeletti P., Bellina, A., Grandori, E., Moretti, A. y Petrini, V. (1988)*. “Comparison between vulnerability assessment and damage index, some results”, Proceedings of the 9th World Conference on Earthquake Engineering, 7, Tokyo, 181-186.

Aoki Y. y Ohaashi Y. (2000). “Target seismic performance levels in structural design for buildings”, Proceedings of 12th World Conference of Earthquake Engineering, Ed. CD-ROM, Nueva Zelanda.

Arias, A. (1970)*. “A measure of earthquake intensity”, Seismic design for nuclear power plants, Hansen, R., MIT Press, Cambridge, Massachusetts, pp. 438-483.

ATC-13: Applied Technology Council (1985). “Earthquake damage evaluation data for California”, Technical Report, Founded by Federal Emergency Management Agency (FEMA), Washington D.C.

ATC-40: Applied Technology Council (1996). “Seismic evaluation and retrofit of concrete buildings, volume 1”, Report: SSC 96-01, Seismic Safety Commission, Redwood City, California.

Atkinson, G. y Silva, W. (2000). “Stochastic modeling of California ground motions”, Bull. Seism. Soc. Am., 90, 255-274.

Atkinson, G. (1993)*. “Earthquake source spectral in eastern North America”, Bull. Seism. Soc. Amer., 83, 1778-1798.

Atkinson, G. M. y Boore, D. (1995)*. “Ground motion relations for Eastern North America”, Bull. Seism. Soc. Amer., 85, 17-30.

Atkinson, G. y Silva, W. (1997)*. “An empirical study of earthquake source spectra for Californian earthquakes”, Bull. Seism. Soc. Amer., 87, 97-113.

Atkinson, G. y Somerville, P. (1994)*. “Calibration of time history simulation methods”, Bull. Seism. Soc. Amer., 84, 400-414.

Bairán, J. (1999). “Efectos de segundo orden y no linealidad en soportes de hormigón armado”, Tesis de Maestría, Universidad de Cantabria, Santander, España.

Bairán, J. (2000). “BCSEC: Programa computacional para el cálculo de características mecánicas no lineales de secciones y piezas arbitrarias”, Departamento de Ingeniería de la Construcción, Universidad Politécnica de Cataluña, Barcelona, España.

Banon, H., Biggs, J. e Irvine, H. (1981)*. “Seismic damage in reinforced concrete frames”, Journal of Structural Engineering, ASCE, 107, 9, 1713-1729.

Barbat, A. y Canet, J. (1994). “Estructuras sometidas a acciones sísmicas”,

Referencias bibliográficas

- 2da. Edición, Edita Centro Internacional de Métodos Numéricos en Ingeniería (CIMNE), Barcelona, España.
- Barbat, A. y Pujades, B. (2004). “Evaluación de la vulnerabilidad y del riesgo sísmico en zonas urbanas. Aplicación a Barcelona”, Proceedings 6º Congresso Nacional de Sismología e Engenharia Sísmica, Guimaraes, Portugal, 229-251.
- Bazán, E. y Meli, R. (1999). “Diseño sísmico de edificios”, Editorial Limusa, México, 317 pp.
- Benedetti, D. y Castoldi, A. (1982)*. “Dynamic and static experimental analysis of stone masonry buildings”, Proceedings 7th European Conference on Earthquake Engineering, Atenas.
- Beresnev, I. y Atkinson, G. M. (1997)*. “Modelling finite-fault radiation from the wn spectrum”, Bulletin of the Seismological Society of America, 87(1), 67-84.
- Bertero, V. (1992). “Lessons learned from recent catastrophic earthquake and associated research”, Primera conferencia internacional Torroja, Madrid.
- Bolt, B. A. (1995)*. “Interplate seismicity and zonation”, Proceedings of the Fifth Pacific Conference on Earthquake Engineering, Melbourne, Australia, 1, 1-11.
- Bommer, J. J. y Martínez-Pereira, A. (1999)*. “The effective duration of earthquake strong ground”, Journal of Earthquake Engineering, 3, pp. 127-172.
- Bonett, R. (2003). “Vulnerabilidad y riesgo sísmico de edificios. Aplicación a entornos urbanos en zonas de amenaza alta y moderada”, Tesis doctoral, Universidad Politécnica de Cataluña. España.
- Bracci, J., Reinhorn, A., Mander, J., y Kunzath, S. (1989). “Deterministic model for seismic damage evaluation of RC structures”, Technical report, NCEER-89-0033, University of New York, Bufalo.

- Brencich, A. y Lagomarsino, S. (1998). "A macroelement dynamic model for masonry shear walls", Technical Report, Computer Methods in Structural Masonry, 4, Editado por G.N. Pande, J. Middleton y B. Kralj.
- Brune, J. N. (1970)*. "Tectonic stress and the spectra of seismic shear waves from earthquakes", Journal Geophysical Research, 75, 4997-5009.
- Bruno, H. y Cotton, F. (2000). "Empirical determination of the ground shaking duration due to an earthquake using strong motion accelerograms for engineering applications", paper No. 2254/4/A, France, pp. 11,
- Bustamante, G., Chatelain, J., Valverde, J., Yepes, H., Tucker, B., Villacis, C., Yamada, T. y Kaneko, F. (1995)*. "An example in Quito, Ecuador, of the use of seismic microzoning for risk reduction in developing countries", Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 683-690.
- Caicedo, C. (1993). "Vulnerabilidad sísmica en zonas urbanas", Tesis doctoral, Universidad Politécnica de Cataluña. España.
- Calvi, G. (1999). "A displacement-based approach for vulnerability evaluation of classes of buildings", Journal of Earthquake Engineering, 3, 3, 411-438.
- Calvi, G.M. (1997). "Un metodo agli spostamenti per la valutazione della vulnerabilità di classi di edifici", L'ingegneria sismica in Italia, Atti VIII Convegno Nazionale ANIDIS, Taormina, Italia. (en italiano).
- Calvi, G.M., Kingsley, G.R. y Magenes, G. (1996)*. "Testing of masonry structures for seismic assessment", Earthquake Spectra, 12, 1, 145-162.
- Carr, A. (1997). "SIMQKE: Artificial earthquake generation", University of Canterbury, Nueva Zelanda.
- Carr, A. (2000). "Inelastic dynamic analysis program: RUAUMOKO and Post-processor for RUAUMOKO: Dynaplot", Department of Civil Engineering, University of Canterbury, Nueva Zelanda.

Referencias bibliográficas

- Carvalho, E. y Coelho, E. (1994). “Global structural behaviour of bare frames”, Bulletin 220, Comite Euro International du Beton, 2, 222-309.
- Chávez, J. (1998). “Evaluación de la vulnerabilidad y riesgo sísmico a escala regional: Aplicación a Cataluña”, Tesis doctoral, Universidad Politécnica de Cataluña. España.
- Chávez, M. y García-Rubio, L. (1995)*. “Seismic vulnerability of the metropolitan zone of Guadalajara, México”, Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 33-40.
- Chiostrini, S. y Vignoli, A. (1989)*. “Application of a numerical method to the study of masonry panels with various geometry under seismic loads”, Structural Repair and Maintenance of Historical Buildings, Computational Mechanics Publications, 309-317.
- Chopra, A.K. y Goel, R.K. (1999). “Capacity-demand-diagram methods based on inelastic design spectrum”, Earthquake Spectra, 15, 4, 637-656.
- Chopra, A.K. y Goel, R.K. (2000). “Evaluation of NSP to estimate seismic deformation: SDF system”, Journal of Structural Engineering, 126, 4, 482-490.
- Chopra, A.K. y Goel, R.K. (2001). “Direct displacement based design: use of inelastic and elastic design spectra”, Earthquake Spectra, 17, 1, 47-65.
- Chung, Y., Meyer, C. y Shinozuka, M. (1987). “Seismic assessment of reinforced concrete members”, Technical report, NCEER-87-0022, National Center of Earthquake Engineering Research, State University of New York, Buffalo.
- Chung, Y., Shinozuka, M. y Meyer, C. (1988). “SARCF User’s guide seismic analysis of reinforced concrete frames”, Technical Report, NCEER-88-0044, Buffalo.
- Chung, Y., Meyer, C. y Shinozuka, M. (1989*). “Modeling of concrete damage”, ACI Structural Journal, 86, 3, 259-271.

- Chung, Y., Meyer, C. y Shinozuka, M. (1990)*. “Automated seismic design of reinforced concrete building frames”, ACI Structural Journal, 87, 3, 326-340.
- Cid, J. (1998). “Zonificación sísmica de la ciudad de Barcelona basada en métodos de simulación numérica de efectos locales”, Tesis doctoral, Universidad Politécnica de Cataluña, pp 215.
- Cid, J., Susagna, T., Goula, X., Chavarria, L., Figueras, S., Fleta, J., Casas, A. y Roca, A. (2001). “Seismic Zonation of Barcelona based on numerical simulation of site effects”, Pure Applied Geophysics, Vol. 158, 1-19.
- Coburn, A. y Spence, R. (2002). “Estimation of the expectes number of casualties”, Earthquake protection, 2da. Edición, John Whiley y Sons.
- Crisafulli (1997). “Seismic behaviour of reinforced concrete structures with masonry infills”, Doctoral thesis, University of Canterbury, Nueva Zelanda.
- CSSC Committee (1999)*. “Earthquake risk management: A toolkit for decision - Makers”, California Seismic Safety Commision, State of California.
- Czarnecki, R.M. (1973)*. “Earthquake damage to tall buildings”, Structures Publication Nº 359, Massachussts Institute of Technology, Department of Civil Engineering, Massachusetts.
- Dhansekar, M. y Page, A. (1986)*. “The influence of brick masonry infill properties on the behaviour of infilled frames”, Proc. Instn. Civ. Engrs., Part 2, 81, 593-605.
- Dhansekar, M., Page, A. y Kleeman, P. (1985)*. “The failure of brick masonry under biaxial stresses”, Proc. Instn. Civ. Engrs., Part 2, 79, 295-313.
- Di Pasquale, G., Goretti, A., Dolce, M. y Martinelli, A. (2001). “Confronto fra differenti modelli di vulnerabilità degli edifici”, Língegneria sismica in Italia, Atti X Convegno Nazionale ANIDIS, Potenza-Matera, Italia. (en italiano).
- Di Pasquale, E. y Cakmak, A. (1987). “Detection and assessment of seismic structural damage”, Technical report, NCEER-87-0015, Bufalo.

Referencias bibliográficas

- DiPasquale, E. y Cakmak, A. S. (1988). "Identification of the serviceability limit state and detection of seismic structural damage", Technical report, NCEER-88-0022, Buffalo, New York.
- DiPasquale, E., Ju, J-W., Askar, A. y Cakmak, A. (1990). " Relation between global damage indices and local stiffness degradation", ASCE Journal of Structural Engineering, 116, 5, 1440-1456.
- Dobry, R., Idriss, I. M. y Ng, E. (1978)*. "Duration characteristics of horizontal components of strong-motion earthquake records", Bulletin Seismological Society of America, 68, pp. 1487-1520.
- Dolce, M., Kappos, A., Zuccaro, G. y Coburn, A. (1994). "Vulnerability and risk analysis: Report of the EAEE working group 3", 10th European Conference on Earthquake Engineering, 4, Viena, 3049-3077.
- Dowrich David (1997). "Earthquake resistant design for Engineers and Architects", 2da. Edición, Edit. John Wiley- Sons, pp. 519.
- Dumova, E. (2000). "Fragility curves for reinforced concrete structures in Skopje (Macedonia) region", Soil Dynamics and Earthquake Engineering, 19, 455-466.
- EERI Committee (1989)*. "The basics of seismic risk analysis", Earthquake Spectra, 5, 4, 675-702.
- Emmi, P. y Horton C. (1993)*. "A GIS-based assessment of earthquake property damage and casualty risk: Salt Lake County, Utah", Earthquake Spectra, 9, 1, 11-33.
- ESRI: Environmental Systems Research Institute (1995). "Understanging GIS", The ARC/INFO Method, John Wiley y Sons, Inc., New York.
- Eurocódigo 2 (1992). "Proyecto de estructuras de hormigón", Parte 1-1: Reglas Generales y Reglas Generales para Edificación, AENOR, España.
- Eurocódigo 6 (1996). "Proyecto de estructuras de fábrica", Parte 1-1: Reglas

para la fábrica armada y sin armar, AENOR, España.

Eurocódigo 8 (1998). “Disposiciones para el proyecto de estructuras sismorresistentes”, Parte 1-1: Reglas generales, acciones sísmicas y requisitos generales de las estructuras, Parte 1-2: Reglas generales, para edificación, AENOR, España.

Eurocódigo 8 (2004). “Design of structures for earthquake resistances - Part 1: General rules, seismic actions and rules for buildings”, EN 1998-1:2004:E, December 2004, 229pp.

EHE-99 Normativa (1999). “Instrucción del Hormigón Estructural”, Ministerio de Fomento, Madrid.

Faccioli, E., Andrigetto, R. y Pessina, V. (1995)*. “Seismic risk zonation and earthquake scenarios using GIS technology”, Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 136-141.

Fajfar P. y EERI M. (2000). “A nonlinear analysis method for performance-based seismic design”, Earthquake Spectra, 3, 16, 573-593.

Fajfar P., Gaspersic, P. y Drobnić D. (1997)*. “A simplified nonlinear method for seismic damage analysis of structures”, Bled Conferenceon Displacement Based Design.

FEMA 273: Federal Emergency Management Agency (1997). “NEHRP Guidelines for the seismic rehabilitation of buildings”, Report No. FEMA-273, Washington, D.C.

FEMA 273: Federal Emergency Management Agency (1997). “NEHRP Commentary on the guidelines for the seismic rehabilitation of buildings”, Report No. FEMA-274, Washington, D.C.

Ferritto, J.M. (1982)*. “An economic analysis of earthquake design levels”, Naval Civil Engineering Laboratory, TN No. N-1640, Port Hueneme, California.

Referencias bibliográficas

- Ferritto, J.M. (1983)*. “An economic analysis of earthquake design levels for new concrete construction”, Naval Civil Engineering Laboratory, TN No. N-1671, Port Hueneme, California.
- FIB Bulletin, Task Group 7.1 (2003). “Seismic assessment and retrofit of reinforced concrete buildings”, Fédération Internationale du Béton (FIB), 24.
- FIB Bulletin, Task Group 7.2 (2003). “Displacement-based seismic design of reinforced concrete buildings”, Fédération Internationale du Béton (FIB), 25.
- Fleta, J., Escuer, J., Goula, X., Olivera, C., Combes, P., Grellet, B. y Granier, T. (1996). “Zonación tectónica, primer estudio de la zonación sismotectónica del NE de la Península Ibérica. (Cataluña)”, Geogaceta, Vol. 20, 853-856.
- Florian, A. (1992). “An efficient sampling scheme: updated latin hypercube sampling”. Probabilistic Engineering Mechanics, 7, 123-130.
- Frankel, A., Mueller, C., Barnhard, T., Perkins, D., Leyendecker, E., Dickman, N., Hanson, S. y Hopper, M. (1996)*. “National seismic hazard maps: documentation June 1996”, U.S. Geol. Surv. Open-File Rept.96-532, pp. 69.
- Freeman, S.A. (1978). “Prediction of response of concrete buildings to server earthquake motion”, ACI Special Publication, SP-55, 589-605.
- Freeman, S.A. (1990). “Development and use of capacity spectrum method”, Proceedings of the 6th National Conference on Earthquake Engineering, EERI, Oakland.
- Galasco, A., Lagomarsino, S. y Penna, A. (2002). “TreMuri program: seismic analyzer of 3D masonry buildings”, Technical Report, Universidad de Génova, Italia.
- Galasco, A., Lagomarsino, S., Penna, A. y Resemini, S. (2004). “Non-linear seismic analysis of masonry buildings”, 13th World Conference on Earthqua-

ke Engineering, paper 843, Vancouver, Canada.

Gambarotta, L. y Lagomarsino, S. (1997). “Damage model for the seismic response response of brick masonry shear walls. Part II: the coninuum model and its applications”, Earthquake Engineering and Structural Dynamics, 26, 441-462.

Gasparini, D. y Venmarcke, E. H. (1976). “Simulated earthquake motions compatible wit prescribed response spectra”, M.I.T., Department of Civil Eng. Research Report R76-4.

Gibson, G. (1993)*. “Artificial ground motion”, Proceedings of a Seminar Held by the Australian Earthquake Engineering Society of the Institute for Engineers Australia, Melbourne, Australia, 83-86.

Giovinazzi, S. y Lagomarsino, S. (2001). “ Una metodologia per lánalisi di vulnerabilità sismica del costruito”, Língegneria sismica in Italia, Atti X Convegno Nazionale ANIDIS, Potenza-Matera, Italia. (en italiano).

Grünthal, G. (1998). “EMS-98: European Macroseismic Scale”, Chaiers dur Centre Européen du Géodynamique et de Séismologie, volume 15, Luxembourg.

Gulkan, P. y Sozen, M. (1974). “Inelastic response of reinforced concrete structures to earthquake motions”, ACI Journal, 71, 12, 604-610.

Gunturi, S. (1992)*. “Buildings specific damage estimation”, PhD Thesis, Stanford University, Stanford.

Hasselman, T., Eguchi, R. y Wiggins, J. (1980)*. “Assessment of damageability for existing buildings in a natural hazards environment”, Volume 1 Methodology, Redondo Beach, California.

Hasselman, T., Eguchi, R., y Wiggins, J. (1980)*. “Assessment of damageability for existing buildings in a natural hazards environment”, Technical Report, No.80-1332-1, J. H. Wiggins Company, California.

Referencias bibliográficas

- HAZUS-99: Earthquake Loss Estimation Methodology (1999). “Earthquake Loss Estimation Methodology, Technical Manual”, Vol. 1, Federal Emergency Management Agency (FEMA), Washington.
- HAZUS-SR2: Earthquake Loss Estimation Methodology - Service Release 2 (1999). “Advanced engineering building module”, Federal Emergency Management Agency (FEMA), Washington D.C.
- Ho, C., Hadj-Hamou, T. y Nilsson, M. (1995)*. “GIS-based zonation of infrastructure damage related to seismically triggered landslide risk”, Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 142-149.
- Hong, H. y Lind, N. (1996). “Approximate reliability analysis using normal polynomial and simulation results”, Structural Safety, 18, 4, 329-229.
- Hou, S. (1968)*. “Earthquake simulation models and their applications”, M.I.T., Department of Civil Eng. Research Report R68-17.
- Huo, J.R., Hu, Y. y Feng, Q. (1991). “Study on the envelop function of the ground motion acceleration time history”, Earthquake Engineering and Engineering Vibration, Vol. 11, No. 1, 1-12.
- Hurtado, J. (1999). “Modelización estocástica de la acción sísmica”, Edita Centro Internacional de Métodos Numéricos en Ingeniería (CIMNE), IS-33, Barcelona, España.
- Hurtado, J.E. (1998). “Stochastic dynamics of hysteresis structures. Application to the seismic analysis of base isolated buildings”. Tesis doctoral, UPC, Barcelona, pp. 206.
- Hurtado, J.E. y Barbat, A. A. (1998). “MonteCarlo simulation techniques in computational stochastic mechanics”, Archives of Computational Methods in Engineering, 5, 3-30.
- Hwan, H. H. M. y Huo, J.R (1994). “Generation of hazard-consistent fragility curves for seismic loss estimation studies”, Technical report, NCEER-94-

0015, Búfalo, Nueva York.

Hwang, H. y Lin, H. (1995)*. “GIS mapping of seismic hazard and seismic risk in Shelby County, Tennessee, USA”, Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 150-157.

Ignatakis, C., Stavrakakis, E. y Penelis, G. (1989)*. “Analytical model for masonry using the finite element method”, Structural Repair and Maintenance of Historical Buildings, Computational Mechanics Publications, 511-523.

Irikura, K. (1986)*. “Prediction of strong acceleration motions using empirical Green’s function”, Proceedings of the 7th Japan Earthquake Engineering Symposium, 151-156.

Irikura, K. y Kamae, K. (1994)*. “Simulation of strong ground motion based on fractal composite faulting model and empirical Green’s function”, Proceedings of the 9th Japan Earthquake Engineering Symposium, Tokyo.

Irizarry, J. (2004). “An advanced approach to seismic risk assessment. Application to the cultural heritage and the urban system of Barcelona”, Tesis doctoral, Universidad Politécnica de Cataluña. España.

Irizarry, J., Goula, X. y Susagna, T. (2003). “Analytical formulation for the elastic acceleration-displacement response spectra adapted to Barcelona soil conditions”, Technical Report, Instituto Cartográfico de Cataluña, pp 48.

Jennings, P. C., Housner, G. W. y Tsai, N. C. (1968)*. “Simulated earthquake motions”, EERL, California Institute of Technology, Pasadena, California.

Joyner, W. B. (1997)*. “Ground motion estimates for the North-eastern U.S. and South-eastern Canada”, In Recommendations for probabilistic seismic hazard analysis: Guidance on uncertainty and use of experts, Senior Seismic Hazard Analysis Committee (R. Budnitz, G. Apostolakis, D. Boore, L. Cluff, K. Coppersmith, A. Cornell and P. Morris eds.), U.S. Nuclear Reg. Comm. Rept. NUREG/CR-6372, Washington, D.C.

Referencias bibliográficas

- Kanai, K. (1957)*. "Semi-empirical formula for the seismic characteristic of the ground", Technical Report 35, Univ. Tokyo, Bull. Earthquake Res. Inst.
- Kappos, A. J. (1992). "Seismic damage indices, criteria for local and global collapse, and their analytical implementation", Technical report, Working Document: CEB Task Group III/2 (Revised version:January).
- Kappos, A., Stylianidis, K. y Michailidis, C. (1992). "Development of earthquake damage scenarios using a comprehensive analytical method", Proceedings of the 10th World Conference of Earthquake Engineering, Madrid.
- Kawamura, H., Tani, A. y Kambara, H. (1992)*. "Aseismic structural planning system by fuzzy network", Proceedings of the 10th World Conference of Earthquake Engineering, Madrid.
- King, S., Kiremidjian, A., Law, K. y basoz, N. (1995)*. "Earthquake damage and loss estimation through geographic system", Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 265-272.
- Kircher, C., Nassar, A., Kustu, O. y Holmes, W. (1997). "Development of building damage functions for earthquake loss estimation", Earthquake Spectra, 13, 4, 663-682.
- Klyanchko, M. (1995)*. "The development of GIS, EQ-DISC and DIMAK as the best tools for seismic risk analysis on the urban areas", Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 158-165.
- Kramer, G. (1996)*. Geotechnical Earthquake Engineering, Prentice Hall, Upper Saddle River, NJ.
- Krawinkler, H. y Alavi, B. (1998)*. "Development of improved design procedures for near-fault ground motions", SMIP98, Seminar on utilization of strong motion data, Oakland, California.
- Kunnath, S., Reinhorn, A. y Lobo, R. (1992). "IDARC version 3.0: A program for the inelastic damage analysis of RC structures". Technical report,

NCEER-92-0022, National Center for Earthquake Engineering Research, State University of New York, Buffalo.

Kunnath, S., Reinhorn, A. y Park Y. (1990). "Analytical modeling of inelastic seismic response of R/C structures", Journal of Structural Engineering, ASCE, 116, 4, 996-1017.

Kustu, O., Miller, D. y Brokken, S.T. (1982)*. "Development of damage functions for high-rise building components", Prepared by URS-John A. Blume y Associates for the U.S. Department of Energy, San Francisco, California.

Lagomarsino, S. y Penna, A. (2003). "Guidelines for the implementation of the II level vulnerability methodology. WP4: Vulnerability assessment of current buildings", Technical presentation RISK-UE project: An advanced approach to earthquake risk scenarios with application to different European towns, Francia.

Lagomarsino, S., Galasco, A. y Penna, A. (2002). "Pushover and dynamic analysis of URM buildings by means of a non-linear macro-element model", International Conference on Earthquake Loss Estimation and Risk Reduction, Technical presentation meeting, RISK-UE project, Bucharest.

Lam, N. T. K., Wilson, J. L. y Hutchinson, G. L. (2000). "Generation of synthetic earthquake accelerograms using seismological modelling: a review", Journal of Earthquake Engineering, Vol. 4, No. 3, 321-354.

Lang, K. (2002). "Seismic vulnerability of existing buildings", Institute of Structural Engineering (IBK), ETH Zurich, Report Nº 273, vdf Hochschulverlag, Zurich.

Lang, K. y Bachmann, H. (2003). "In the seismic vulnerability of existing unreinforced masonry buildings", Journal on Earthquake Engineering, 7, 3, 407-426.

Lantada, N. (2006). "Aplicación de técnicas GIS para estimación de riesgos naturales. Riesgo sísmico", Tesis doctoral, Universidad Politécnica de Cata-

Referencias bibliográficas

- luña. (En preparación).
- Lantada, N., Pujades, L. y Barbat, A. (2004) . “Risk scenarios for Barcelona, Spain”, 13th World Conference on Earthquake Engineering, paper 423, Vancouver, Canada.
- Lawson, S., Anagnos, T., Kircher, C. y Shah, H. (1995)*. “Development of a regional earthquake loss estimation methodology”, Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 281-289.
- Liu, S. C. (1968)*. “On intensity definitions of earthquakes”, Journal of Structural Division, ASCE.
- Lofti, H. R. (1994)*. “Finite element analysis of fracture of concrete and masonry structures”, Ph.D. Thesis, Department of Civil, Environmental and Architectural Engineering, University of Colorado, Boulder.
- Lourenço, P. B. (1994)*. “Analysis of masonry structures with interface elements: Theory and applications”, Delft University of Technology, Report No. 03-21-22-0-01, Delft, Netherlands.
- Mahdyiar, M., Cornell, A., Jackson, D. y Aki, K. (1995). “Probabilistic seismic hazard analysis of southern California”, Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 453-461.
- Mañà, F. (1997). “Vulnerabilitat sísmica dels edificis de la ciutat de Barcelona”, Institut de Tecnología de la Construcción de Catalunya. España.
- Marí, A., Alegre, V., Gens, A., Roca, P. y otros (2003). “Estudio preliminar sobre los posibles efectos de la construcción de un túnel para el tren de alta velocidad bajo los edificios situados entre las calles Mallorca, Valencia, Lepanto y Cartagena”, Universidad de Barcelona.
- McGuire, R. K. (1978)*. “A simple model for estimating Fourier amplitude spectra of horizontal ground acceleration”, Bull. Seism. Soc. Amer., 68 (3), 803-822.

Mena, U. (2002). “Evaluación del riesgo sísmico en zonas urbanas”, Tesis doctoral, Universidad Politécnica de Cataluña. España.

Moehle J. (1992). “Displacement-Based design of RC structures subjected to earthquakes”, Earthquake Spectra, 3, 4, 403-428.

Molins i Borrell, C. (1996). “Un modelo para el análisis del comportamiento resistente de construcciones de obra de fábrica”, Tesis doctoral, Departamento de ingeniería de la construcción, Universidad Politécnica de Cataluña, España.

Moreno R., Bairán J., Pujades L., Aparicio A. and Barbat A. (2004)a. “Evaluación probabilista del comportamiento sísmico de edificios porticados de hormigón armado”, Revista Hormigón y Acero, Vol. 232, pp. 125-136.

Moreno, R., Pujades L., Barbat A. y Aparicio A. (2004)b. “Influence of masonry infills walls on the seismic behaviour of multi-storey waffle slabs RC buildings”, 13th World Conference on Earthquake Engineering, paper 209, Vancouver, Canada.

Moreno, R., Bonett, R., Barbat, A., Pujades, L., Penna, A. y Lagomarsino, S. (2003)a. “Evaluación de la vulnerabilidad sísmica de estructuras de mampostería no reforzada. Aplicación a un edificio de la zona del Eixample en Barcelona (España)”, Revista Internacional de Ingeniería de Estructuras, Ecuador, Vol 8, 2, 91-120.

Moreno, R., Lantada, N., Bonett, R., Barbat, A. y Pujades, L. (2003)b. “WP4: Vulnerability assessment of current buildings. Capacity and fragility of the Barcelona’s residential buildings”, RISK-UE project: An advanced approach to earthquake risk scenarios with application to different European towns, Technical presentation CIMNE Group.

Nau, R., Oliver, R. y Pister, K. (1982). “Simulating and analyzing artificial nonstationary earthquake ground motion”, Bull. Seism. Soc. Amer., 72, 2, 615-636.

Referencias bibliográficas

- NBE-AE-88 Normativa (1998). “Norma Básica de la Edificación”, Ministerio de Fomento, 5ta reimpresión, Madrid.
- NCSE-02 Normativa (2002). “Norma de Construcción Sismorresistente: Parte General y Edificación”, Real Decreto 997/2002, Boletín Oficial del Estado: 244. Madrid.
- NCSE-94 Normativa (1994). “Norma de Construcción Sismorresistente: Parte General y Edificación”, Real Decreto 2543/94, Boletín Oficial del Estado: 33, Madrid. Acciones en la edificación, Series normativas, Norma básica de la edificación, AE-88, Ministerio de Fomento, pp. 77-135.
- OAK Engineering Inc. (1994)*. “Development of damage functions for buildings”.
- Otani, S. (1974)*. “Inelastic analysis of RC frame structures”, Journal of Structural Division, ASCE, 100 (ST7), 1433-1449.
- Otani, S. (1981). “Hysteresis models of reinforced concrete for earthquake response analysis”, Journal Faculty of Engineering, XXXVI, 2, 2, Universidad de Tokio.
- Page, A. W. (1978)*. “Finite element model for masonry”, Journal of the Structural Division ASCE, 104, ST 8, 1267-1285.
- Paret, T.F., Sasaki, K.K., Eilbekc, D.H. y Freeman, S.A. (1996). “Approximate inelastic procedures to identify failure mechanisms from higher mode effects”, Proceedings of 11th World Conference of Earthquake Engineering, Acapulco, México.
- Paricio C., A. (2001). “Secrets d'un sistema constructiu: l'Eixample”, Ediciones UPC, Aula de Arquitectura, Universidad Politécnica de Cataluña, pp. 100.
- Park, R. y Paulay, T. (1994). “Estructuras de concreto reforzado”, Edit. Limusa, 2da. Edición, México.

- Park, Y. J., Ang, A. H-S. y Wenn, Y. K. (1987). "Damage limiting aseismic design of buildings", *Earthquake Spectra*, 3, 1, 1-26.
- Park, Y. y Ang, A. (1985a). "Mechanistic seismic damage model for reinforced concrete", *Journal of Structural Engineering, ASCE*, 111, 4, 722-739.
- Park, Y. y Ang, A. (1985b). "Seismic damage analysis of reinforced concrete buildings", *Journal of Structural Engineering, ASCE*, 111(4), 740-757.
- Paulay, T. y Priestley, M.J.N. (1992). "Seismic design of reinforced concrete and masonry structures", John Wiley & Sons, New York.
- Paz, M. (1997). "Structural dynamics, theory and computation", Edit. Chapman y Hall, 4ta. Edición, EEUU.
- PDS-1 (1974). "Norma sismorresistente P.D.S.-1", Presidencia de Gobierno, Comisión Interministerial, Decreto 3209, Madrid, España.
- Penna, A. (2002). "A macro-element procedure for the non-linear dynamic analysis of masonry buildings", Tesis de doctorado, Politécnico de Milano, Italia.
- Petrini, L., Pinho, R. y Calvi, G.M. (2004). "Criteri di progettazione antisismica degli edifici", IUSS Press, Pavia.
- Petrovski, J., Ristic, D. y Nocevski, N. (1992)*. "Evaluation of vulnerability and potential seismic risk level of buildings", Proceedings of 10th World Conference of Earthquake Engineering, Madrid.
- PGS-1 (1968). "Norma sismorresistente PGS-1", Presidencia de Gobierno, Comisión Interministerial, Decreto 106/1969, Madrid, España.
- Pinto, P., Giannini, R. y Franchin, P. (2004). "Seismic reliability analysis of structures". IUSS Press, Pavia.
- Priestley M. (2000). "Performance based seismic design", Keynote address, Proceedings of 12th World Conference on Earthquake Engineering, Auckland.

Referencias bibliográficas

- Priestley M.J.N. (2003). "Myths and fallacies in earthquake engineering, revisited", The Mallet Milne Lecture, IUSS Press, Pavia.
- Priestley, M.B. (1981)*. "Spectral analysis and Time Series", Academic Press, London.
- Regalado, F. (2003). "Los forjados reticulares" CYPE Ingenieros, España, 255 pp.
- Reinhorn, A., Seidel, M., Kunnath, S. y Park, Y.(1988). "Damage assessment of reinforced concrete structures in Eastern United States", Technical report, NCEER-88-0016, University of New York, Bufalo.
- Restrepo, L. (2004). "Seismic risk of unreinforced masonry buildings", Ph.D. Thesis, Rose School, Università degli Studi di Pavia, Italia.
- Riddington, J. R. y Ghazali, M. Z. (1990)*. "Hypothesis for shear failure in masonry joints", Proc. Instn. Civ. Engrs., Part 2, 89, 89-102.
- RISK-UE Project of the European Commission (2004). "An advanced approach to earthquake risk scenarios with applications to different European towns", contract number: EVK4-CT-2000-00014.
- Rodriguez-Makek, A. (2000)*. "Near-fault seismic site response", PhD. Thesis, Department of Civil Engineering, University of California, Berkeley.
- Roufaiel, M. y Meyer, C. (1987). "Analytical modelling of hysteretic behaviour of R/C frames", Journal of Structural Division, ASCE, 113, 3, 429-444.
- Safina, S. (2002). "Vulnerabilidad sísmica de edificaciones esenciales, análisis de su contribución al riesgo sísmico", Tesis doctoral, Universidad Politécnica de Cataluña. España.
- Samarasinghe, W., Page, A. y Hendry, A. (1982)*. "A finite element model for the in-plane behaviour of brickwork", Proc. Instn. Civ. Engrs., 71, 2, 171-178.

Sasani, M. y Bertero, V. (2000)*. "Importance of severe pulse-type ground motion in performance-based earthquake engineering: historical and critical review", Proceedings of the 12th World Conference on Earthquake Engineering, Nueva Zelanda.

SEAOC (1995). "Vision 2000 a framework for Performance-Based Engineering", Structural Engineers Association of California, California.

Secanell, R., Goula, X., Susagna, T., Fleta, J. y Roca, A. (2004). "Seismic hazard zonation of Catalonia, Spain, integrating uncertainties", Journal of Seismology, Vol. 8, 24-40.

Singhal, A. y Kiremidjian, A. (1995). "Method for developing motion damage relationship for reinforced concrete frames", Technical report, NCEER-95-0008, Búfalo, Nueva York.

Somerville, P. (1998)*. "Development of an improved representation of near-fault ground motions", Proceedings, SMIP98, Seminar on utilization of strong motion data, California Strong Motion Instrumentation Program, Sacramento, California, 1-20.

Somerville, P., Smith, N., Graves, R. y Abrahamson, A. (1997)*. "Modification of the empirical strong ground motion attenuation relations to include the amplitude and duration effects of rupture directivity", Seismological Research Letters, 68, 199-222.

Sorrentino, L. y Masiani, R. (2003)*. "Dynamic out-of-plane behaviour of unreinforced masonry walls", Proceedings 6th International Symposium on Computer Methods in Structural Masonry, Roma.

Stewart, J., Bray, J., Somerville, P. y Abrahamson, N. (2001)*. "Ground motion evaluation procedures for performance-based design", PEER Report, Richmond, California.

Susagna, T. y Goula, X. (1998). "Catàleg de sismicitat. Atlas sísmic de Catalunya", Institut Cartogràfic de Catalunya, Vol. 1.

Referencias bibliográficas

- Tajimi, H. (1960)*. "A statistical method of determining the maximum response of a building structure during an earthquake", Proc. 2ºWCEE, vol. 2, Tokyo y Kyoto, 781-798.
- Takeda, T., Sozen, M. y Nielsen, N. (1970). "R/C response to simulated earthquakes", Journal of Structural Division, ASCE, 96 (ST12), 2557-2573.
- Thibault, C. y Velkok, P. (1995)*. "Evaluation of seismic vulnerability of an urban neighbourhood in Nice", Proceedings of the 5th International Conference on Seismic Zonation, Nice, 1, 92-100.
- Tomažević, M. (1997). "Seismic resistance verification of masonry buildings: following the new trends", Fajfar y Krawinkler editores, Rotterdam, 323-334.
- Trifunac, M. D. (1976)*. "Preliminary empirical model for scaling Fourier amplitude spectra of strong ground acceleration in terms of earthquake magnitude, source-to-station distance and recording site conditions", Bull. Seism. Soc. Amer., 66 (4), 1343-1373.
- Trifunac, M. D. (1989)*. "Dependence of Fourier spectrum amplitudes of recorded earthquake accelerations on magnitude, local soil conditions and on depth of sediments", Earthq. Engrg. Struct. Dyn., 18, 999-1016.
- Trifunac, M. D. y Brady, A. G. (1975)*. "A study on the duration of strong ground motion", Bulletin Seismological Society of America, 65, pp. 581-626.
- USGS*. " National Earthquake Information Center, World data Center a for Seismology".
- Venmarcke, E. H. (1976)*. "Seismic risk and engineering decisions", Chapter 8, Editor: Lomnitz, C. and Rosenblueth, E., Elsevier Publishing Co.
- Villegas, L. (1992). "Estructuras de fábrica: Apuntes docentes", Universidad de Cantabria. España
- Whitman, R.V., Tarek, S. y Wong, E. (1977)*. "Preliminary correlations between earthquake damage and strong ground motion", Structures Publi-

cation N° 564, Massachussets Institute of Technology, Department of Civil Engineering, Massachusetts.

Wilson, E. y Habibula, H. (2002). “SAP2000: Static and dynamic finite element analysis of structures non linear”, Computers and Structures, Inc. Berkeley, California, USA.

Wong, E.H. (1975)*. “Correlations between earthquake damage and strong ground motion”, Massachussets Institute of Technology, Department of Civil Engineering, Massachusetts.

Yépez, F. (1996). “Metodología para la evaluación de la vulnerabilidad y riesgo sísmico de estructuras aplicando técnicas de simulación”, Tesis doctoral, Universidad Politécnica de Cataluña. España.

Zárate, F., Hurtado, J., Oñate, E. y Rodríguez, J. (2002). “STAC program: Stochastic analysis computational tool”, CIMNE, Centro Internacional de Métodos Numéricos en la Ingeniería, Barcelona, España.

Páginas web citadas:

<http://www.angelfire.com/nt/placas>

<http://www.chez.com/bhernand/wcee00.html>

<http://www.icc.es>

<http://www.lablaa.org>

<http://www.snet.gob.sv>

<http://www.neic.cr.usgs.gov.>